

(NOTES CONTINUED)

TAKEOFF MINIMUMS:

- Rwy 4L/R: Standard. ATC climb of 500' per NM to 2500.
- Rwy 11: Standard with minimum climb of 361' per NM to 2500.
- Rwy 22L: Standard with minimum climb of 453' per NM to 500.
- Rwy 22R: Standard with minimum climb of 459' per NM to 400.
- Rwy 29: Standard with minimum climb of 473' per NM to 500.

TAKEOFF OBSTACLES NOTES:

- Rwy 4L: Tower, light, and multiple trees beginning 211' from DER, 198' left of centerline, up to 70' AGL/89' MSL.
DME antenna and pole beginning 881' from DER, 418' right of centerline, up to 121' AGL/131' MSL.
- Rwy 4R: DME antenna, tree, and multiple towers beginning 530' from DER, 477' left of centerline, up to 61' AGL/82' MSL.
Tower, sign, tree, multiple buildings and poles beginning 1134' from DER, 153' right of centerline, up to 121' AGL/131' MSL.
- Rwy 11: Pole, tree, and multiple signs beginning 6' from DER, 158' right of centerline, up to 31' AGL/50' MSL.
Sign, tree, road, fence, building, and multiple poles beginning 82' from DER, 2' left of centerline, up to 49' AGL/68' MSL.
- Rwy 22L: Pole 8' from DER, 261' left of centerline, 7' AGL/16' MSL.
- Rwy 22R: Light and multiple trees beginning 1829' from DER, 307' right of centerline, up to 55' AGL/69' MSL.
Building 1.4 NM from DER, 1872' left of centerline, 200' AGL/227' MSL.
- Rwy 29: Multiple poles, trees, signs, and buildings beginning 209' from DER, 242' left of centerline, up to 110' AGL/120' MSL.
Tree, multiple signs and poles beginning 689' from DER, 66' right of centerline, up to 273' AGL/358' MSL.
Building 6029' from DER, 1624' right of centerline, 273' AGL/357' MSL.
Building 1.5 NM from DER, 2071' right of centerline, 202' AGL/328' MSL.

NE-2, 06 FEB 2014 to 06 MAR 2014

NE-2, 06 FEB 2014 to 06 MAR 2014